



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶: F24C 7/08, 15/02	A1	(11) International Publication Number: WO 97/26486 (43) International Publication Date: 24 July 1997 (24.07.97)
(21) International Application Number: PCT/DK97/00027 (22) International Filing Date: 20 January 1997 (20.01.97) (30) Priority Data: 0055/96 19 January 1996 (19.01.96) DK (71) Applicant: AKTIEBOLAGET ELECTROLUX [SE/SE]; Luxbacken 1, Lilla Essingen, S-105 45 Stockholm (SE). (71)(72) Applicants and Inventors: ÖSTLUND, Pelle [SE/SE]; Ankdammsgatan 22, S-171 43 Solna (SE). ESKILDSEN, Christian [DK/DK]; Dammen 14, DK-5591 Gelsted (DK). (74) Agent: BROCK-NANNESTAD, George; Electrolux EPDH Tech-Centre, Sjaellandsgade 2, DK-7000 Fredericia (DK).		(81) Designated States: AL, AM, AT, AT (Utility model), AU, AZ, BB, BG, BR, BY, CA, CH, CN, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i>
(54) Title: A CONTROL DEVICE FOR A DOMESTIC OVEN (57) Abstract <p>Controls for ovens and cooking ranges are traditionally rotary knobs or electronic controls embedded in the outer surface of the equipment. According to the invention, the controls are fitted into the handle for the door of an oven, e.g. by providing rotary controls at the extremities of a rod-shaped handle or by push-actuators along the rod. The electrical contact is made by means of a cable through the hinges or by multipoint connectors which are only active when the door is closed which provides additional safety features. In the latter case, the entire door may be removed without the need for separation of the electrical circuit.</p> <div data-bbox="776 1178 1365 1654" data-label="Image"> </div>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NR	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

A control device for a domestic oven.

The invention relates to a control device, in particular a signal input device for the functions of an oven for the preparation of food.

Most controls for ovens and cooking ranges were traditionally rotary knobs which directly acted on the supply of energy, e.g. electrical power or gas as in a switch or tap. With the advent of remote control by electrical signal it became possible to place the controls independently of the actual switches, i.e. there is no longer any need for a mechanical linkage from the manual actuating device to the switch or tap. Electronic solutions are now used, and their greatest limitation is that some parts will be placed in heated areas which reduces the lifetime of electronic components. It is also now desired to have a still greater freedom in the placement of controls, and this is obtained by using a data bus structure connecting a control signal input device, such as a knob, touch switch, proximity switch or the like, to the energy controller and also the thermostats used for ovens and cooking plates.

It is the purpose of the invention to provide an input device for the control signals for in particular ovens which provides greater flexibility than has previously been attainable and which permits a truly ergonomic approach permitting the consumer to control an apparatus which will in use become dangerously hot in places.

This obtained in a control device which is particular in that it is incorporated in the handle for the oven door, in particular in its extremities.

This construction will give the following distinct advantages over previously known constructions:

The oven cavity with its door will not need any auxiliary control panel and may hence be placed with

CONFIRMATION COPY

great flexibility within a kitchen environment takning only the ususal care with enclosing a hot environment.

All the control electronics except that which is actually controlling the supply of energy may be put in the handle along with the input devices which means that they are all in a relatively cool environment.

Contact to the control electronics may be established via connections created through the hinge which will operate both when the oven door is closed and when open. Alternatively connections may be established by the mating of contact surfaces when closing the oven door. This brings the further advantage that turning on e.g. a hot air oven is only performed when the door is closed. When the oven door is open the necessary power supply to the control electronics may be had from a rechargeable battery or super capacitor also stored in the handle. In this case, the entire door may be removed without the need for separation of the electrical circuit.

By establishing contact from the input device and the control electronics to the data bus by means of an infrared link, only the power supply to the electronics in the handle must be fed by wire.

The invention will be further described with reference to the drawing, in which

Fig. 1 from the side shows an oven door in its closed position,

Fig. 2 from the side shows an oven door in its open position,

Fig. 3 shows a front view of one embodiment of the invention, and

Fig. 4 shows a second embodiment of the invention with push buttons.

In Fig. 1 is shown the front part of an oven cavity 1, being closed by an oven door 2 which is only shown schematically. Usual practice of using a double-glazed insulating construction may be adhered to. The

door is hinged by means of hinges 3, and near the top it is fitted with a bar-shaped handle 4. A push-button 5 is indicated at the visible end of the handle 4. Also indicated is an electrical connection between the handle 5 4 and the door frame at the spot 6 which represents a multiconductor or multipoint galvanic contact. The same features are shown at Fig. 2, only the door is open, and the galvanic connection to the spot 6 is broken. Alternatively or simultaneously, an electrical 10 connection which is not shown may be made permanently by passing it through the hinge.

In Fig. 3 is shown that the control signal input devices on the handle 4 are rotary ends 7 and 7' of the handle extremities. The left hand rotary device 7 may 15 control the temperature, and the right hand rotary device 7' may control the time of heating.

In Fig. 4 is shown an alternative and more elaborate disposition of the input devices, in that they are buttons 8 disposed along the length of the handle. 20 Also shown is a small display 9, such as a temperature indicator. Alternatively, the display may show the status of any one button being pushed.

P A T E N T C L A I M S

1. A control device for the functions of an oven
for the preparation of food comprising an oven cavity
5 which may be closed by an oven door,
c h a r a c t e r i z e d i n that the control
device is incorporated in the handle for the oven door,
in particular in its extremities.

2. A control device according to claim 1,
10 c h a r a c t e r i z e d i n that all necessary
control electronics is placed in the handle along with
the input devices.

3. A control device according to claim 1 or 2,
c h a r a c t e r i z e d i n that contact to the
15 control electronics is established via connections
through one or both of the hinges for the door.

4. A control device according to claim 1 or 2,
c h a r a c t e r i z e d i n that connections to
the control electronics are established by the mating of
20 contact surfaces when closing the oven door.

5. A control device according to claim 4,
c h a r a c t e r i z e d i n that the necessary
power supply to the control electronics in the open
state of the oven door is provided by a re-chargeable
25 battery or super-capacitor held inside the handle

6. A control device according to any of the claims
3 to 5, c h a r a c t e r i z e d i n that
communication between the input device and the control
electronics occurs by means of an infrared link.

30 7. A control device according to any of the above
claims, c h a r a c t e r i z e d i n that the
control device in the handle communicates with a data
bus for the oven installation.




Fig. 1




Fig. 2




Fig. 3





Fig. 4

INTERNATIONAL SEARCH REPORT

International application No.

PCT/DK 97/00027

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: F24C 7/08, F24C 15/02

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: F24C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	Patent Abstracts of Japan, Vol 14, No 545, M-1054, abstract of JP,A,2-230026 (SANYO ELECTRIC CO LTD.), 12 Sept 1990 (12.09.90) --	1-3,7
X	Derwent's abstract, No 94-239969/29, week 9429, ABSTRACT OF SU, 1812392 (TULA TECHN INST), 30 April 1993 (30.04.93) --	1-3,7
X	Patent Abstracts of Japan, Vol 11, No 301, M-628, abstract of JP,A,62-91729 (MATSUSHITA ELECTRIC IND CO LTD.), 27 April 1987 (27.04.87) --	1

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

17 April 1997

Date of mailing of the international search report

18.04.97

Name and mailing address of the ISA/
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Authorized officer

Anders Bruun
Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.

PCT/DK 97/00027

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	Patent Abstracts of Japan, Vol 8, No 47, M-280, abstract of JP, A, 58-200940 (MATSUSHITA DENKI SANGYO K.K.), 22 November 1983 (22.11.83) --	1
A	EP 0362130 A1 (GIGATHERM AKTIENGESELLSCHAFT), 4 April 1990 (04.04.90) -- -----	

04/03/97

PCT/DK 97/00027

Form PCT/ISA/210 (patent family annex) (July 1992)